

Edge3i

High performance plaster-up-to loudspeaker

DATASHEET Rev. 1.1 | 01-06-2020 | E&OE

amina.


Product Description

First launched in 2017, the award-winning high-sensitivity Edge series of plaster-up-to invisible loudspeakers have become synonymous with low frequency impact and a truly engaging listening experience. The 'i' update provides significant acoustic upgrades with the introduction of brand new proprietary high frequency transducers. Packaged into a smaller footprint and using the same tapered perimeter glass resin core as the larger Edge5i and Edge7i loudspeakers, the Edge3i provides exceptional performance at a cost-efficient price point. Designed for installation into dryline walls and ceilings as well as a retrofit into plaster finished surfaces.

Example Applications

Medium-power residential/commercial distributed audio solutions and multi-channel surround sound systems when used with a subwoofer. Designed to be installed into dryline walls & ceilings, but may also be used as a post-plaster retrofit in applications with a plaster skim coat. Can be supplied with high-impedance 100/70V transformer.

Frequency Response



Specifications

Edge3i

Nominal impedance	8 Ohms
Power handling (100 hour continuous/peak)	30W/60W
Sensitivity (@ 1m/2.83Vrms)	86dB SPL
Frequency response (-6dB)	90Hz - 25kHz
Usable frequency range (+/-10dB)	65Hz - 30kHz
Dispersion angle	180° x 180° at specified frequency range
Electrical connection	Blue butt-splice crimp terminals (14-16 AWG)
Dimensions	400mm x 300mm x 36mm (15 ^{3/4} " x 11 ^{13/16} " x 1 ^{7/16} ")
Product weight	1kg (2lb 3oz)
Fixing requirements	Backbox CV300 or Mounting Blocks
In-line protection unit	APUi30C, APU-RS8iC or APU-RS16iC
Manufacturer limited warranty	10 years

Amina Technologies Limited

Cirrus House, Glebe Road, Huntingdon, Cambridgeshire, PE29 7DL, England
T: +44 (0) 1480 354390 | E: info@aminasound.com | W: www.aminasound.com